

Digital Temperature Sensor




Controls the trailer temperature in real-time over the Internet, avoiding interruptions to the cold chain. Alarms can be displayed when values exceed preset limits.


- It is compliant with EC REGULATION No. 1/2005 OF THE COUNCIL, dated 22 December 2004, governing the protection of animals during transport and associated operations, modifying Directives 64/432/EEC and 93/119/EC of EC Regulation No. 1255/97

Benefits

- Offers vital information for companies that use refrigerated vehicles and transport perishable goods.
- Displays the cargo temperature in real-time and allows immediate action in the case of an incident, providing value added for the company and a guarantee for customers.
- The temperature reports can be used as a certificate of guarantee in case of complaints.
- Thanks to this tool, fleet managers can reduce haulage insurance costs.



The graph generated from the reports provides an immediate display of when and for how long the cold chain was broken



The report generated displays the exact time and place of a fault in the temperature recorded by the sensors

Technical specifications

Sensor temperature range	From -55°C to +125°C
Resolution	0.1°C
Accuracy	± 0.5°C
Consumption	Under normal conditions: 2 mA
Housing type	IP65

Physical specifications

Box dimensions	62 x 62 x 33 mm
Metal bar dimensions	70 mm long and 6 mm in diameter

Option for connecting several at the same time.

Doors-Open and Humidity Sensor





The humidity sensor is installed in the vehicle trailer to measure relative humidity

- It is compliant with EC REGULATION No. 1/2005 OF THE COUNCIL, dated 22 December 2004, governing the protection of animals during transport and associated operations, modifying Directives 64/432/EEC and 93/119/EC of EC Regulation No. 1255/97



The doors-open sensor can be used to detect when the vehicle doors are opened or closed, determining when and where the event occurs.

This heavy-duty device is made of aluminium and is easy to install. It provides control and security for the cargo being transported.



A simple report ensures that your most delicate goods are being transported under optimal conditions